

Options for Flood Risk Management on the Thames Estuary

David Ramsbottom HR Wallingford





Development of the Options

High Level Options

Several climate change scenarios

Demonstrate how climate change can be managed

Consultation Options

Designed for one climate change scenario


Adaptable

Defence deterioration, repair and replacement

Feasible designs




The Thames Estuary







The Thames Estuary



TE2100 scenarios for sea level rise







Main responses to flood risk


Over-rotate / improve Thames Barrier New barriers / barrages / throttles Raise defences / new defences Storage of floodwater

Floodplain Management

Flood incident management and recovery Existing and new development


Responses to fluvial flooding (West London, tributaries)






















Note:


Each box represents one or more portfolios of responses


The arrows indicate paths for adapting options for different sea level ranges


The High Level Options











The 'Drivers' of change

Climate

Asset condition (and deterioration)

Socio economic conditions

The physical environment

Public attitudes and expectations

'Drivers' can be represented by 'indicators' (things that can be measured)




Indicator value

(e.g. sea level rise)

Thresholds, lead times and decision points

Threshold value of indicator when intervention is needed




Time

Indicator value


(e.g. sea level rise)

Thresholds, lead times and decision points

Threshold value of indicator when intervention is needed



Time




Threshold 1: Limit of present system

Threshold 2: Limit of Thames Barrier

Threshold 3: Limit of Thames Barrier with over-rotation or flood storage

Responses for increases in maximum sea level (from Thames Barrier downriver)



Note:

The portfolios of responses are designed to keep the annual number of closures below 70.

Thus the actual number of closures follows the dotted brown lines.

Impact of Mean Sea Level increase on defences upriver of the Thames Barrier

An option



Main Assumptions

Policy Iteration B (P5 introduced in 2080)

Defra climate change

70 Barrier closures per year

Perfect forecasting accuracy


New infrastructure: London Gateway port

1050ha habitat needed by 2100

	Indicators	Epoch																		
Option		2000	2010	2020	2030	2040	2050	2060	2070	2080	2090	2100	2110	2120	2130	2140	2150	2160	2170	2180
Option 1	Extreme tidal WL			Raise d/r defences Improve TB and raise downriver defences										nces						
	Extreme tidal WL						Trial flood storage area (Aveley)													
	Thames flow				Raise West London defences including demountables; receptor responses															
	Barrier closures										Raise u/s 0.5m			Raise u/s 0.5m			N	New barrage		
	New port		N	navig	vigation constraint downriver of new port															
	Habitat area				1050ha managed realignment Further habitat creation									1						

Each coloured bar represents a response (or portfolio of responses)
All the coloured bars make up an option


An option



Each coloured bar represents a response (or portfolio of responses)
All the coloured bars make up an option

The diagram shows the timing of decisions for a complete option

Impact of change on Decision Points





Main Assumptions

Policy Iteration B (P5 introduced in 2080)
Defra climate change
70 Barrier closures per year

Perfect forecasting accuracy


New infrastructure: London Gateway port

Updated option

Legend

Implementation point

Decision point



Effect of monitoring is to change decision dates

Change could affect timing of interventions or (if change is large), choice of option

Adaptation

Changes in timing of interventions Changes in choice of interventions Adaptable interventions

Defence foundations for future raising

Alternative defence alignments

Future conversion of structures

'Precautionary' land use planning:

Safeguard land for Flood Risk Management

Space for future improvement



Monitoring (examples)

Mean Sea Level / Maximum surge tide level

Fluvial flood flows

Annual number of Barrier closures

Condition of defences

Area of habitat

Extent/value of development

Public attitudes

Plus updated predictions of change and Government Guidance



The current Estuary-Wide Options

- Improve defences
- 2. Tidal flood storage
- 3. New Barrier: 2 locations
- 4. New Barrier with locks: 3 locations

Floodplain management and other local options are covered in the PMU options

Final Plan may include a combination of options



All options include:

Managed realignment

Local responses for fluvial flood risk:

West London

Tributaries

Floodplain management

Creating a better place



Local Area (PMU) options....

Achieve requirements for estuary-wide options

Cover other sources of flooding (e.g. tributaries, drainage systems)

Include floodplain management

Include opportunities to create a better place



Floodplain management

Flood forecasting & warning

Pre-event measures including emergency planning

Spatial planning for existing development

Community based measures

Safe havens, high level access

Secondary defences


Spatial planning for new development

Development layout

Resilient construction

Move vulnerable development







The floodplains

An example from the Netherlands

Dordrecht Floodproof Pilot © Baca Architects













The End

Thank you

